



# ENERGEX® INSTAGLIDE® THHN/THWN-2/MTW

Master any challenging installation with ENERGEX® INSTAGLIDE® THHN/THWN-2/MTW, a general-purpose cable for use in power, lighting and control circuits.

## Standards

- Cables are UL listed as Type THHN/THWN-2/MTW
- Meets UL VW-1 flame test requirements
- THHN/THWN-2 90°C rated for wet and dry locations
- MTW rated 90°C in dry locations & 60°C in wet locations or when exposed to oil/coolants
- Gasoline and Oil Resistant II
- UL 83: Thermoplastic Insulated Wires and Cables
- UL 1063: Machine Tool Wires and Cables (stranded cables only)
- Rated 600 volts

## Versatile

- PVC Insulation with Nylon Covering: INSTAGLIDE® reduced friction construction in sizes 6 AWG and larger
- Significantly easier to pull and control through conduit, ducts and trays for service feeders and branch circuits in industrial & commercial installations
- Sizes 8 AWG to 600 kcmil available in various colors from stock
- Conductor sizes 1/0 AWG and larger (4 AWG and larger in green) are rated CT use
- Black sizes 1/0 AWG and larger are sunlight resistant
- Clean — no oily residue on your hands, tools and equipment



Made in USA

**ENERGEX® INSTAGLIDE® THHN/THWN-2/MTW pulls smoothly, saving time and money!**

For more information, please contact us: 1-866-6-NEXANS | [www.nexans.us](http://www.nexans.us)

ENERGEX® & INSTAGLIDE® are registered trademarks of Nexans.

  
BRINGS ENERGY TO LIFE